

BOLT ON LOCKS WITH FOREND



SPECIFICATION SHEET

174

- Ⓜ This variation of the Select Pro range has a lockcase without the projecting security escutcheons on each side and is fitted with a stainless steel forend plate.
- Ⓜ These locks can be fitted into a mortise on the edge of a gate or door. They are ideal for use on wooden gates where the long 30mm throw gives plenty of tolerance.
- Ⓜ Supplied with a stainless steel forend plate, keep plate, 90mm long Eurocylinder and 2 screw fixed flat escutcheons.



PRODUCT OPTIONS

All our Select Pro range are available with as a forend version.

- SBD1601F** - Deadlock with forend
- SBLD1601F** - Latch deadlock with forend
- SBKL1601F** - Keylatch with forend
- SBKLLT1601F** - Long throw keylatch with forend



DEADLOCK



KEYLATCH

INSTALLATION

Mortise the timber to take the lock body. Cut holes for the eurocylinder to slide through the lock. Install lock and fix with 4 screws through the forend plate.

Lock size - H x D x W
- 110 x 98 x 30

MAINTENANCE

Every 2 months - Lubricate latchbolt with light oil.
Annually – Dismantle lock and spray mechanism inside with light oil.



VISIT GATEMASTERLOCKS.COM FOR MORE INFORMATION

